

PODIAFLUX®

FLOWING RESIN

1 - Description of material

Podiaflux® is for use mainly as a base (or built-in reinforcement). Excellent for thermowelding, developed in 1986 by foot therapists.

2 - Technical information

The polyester resin of choice because of its flowing ability. Does not contain latex.

| Thermoformability | 1 2 3 4 5 |
|-------------------|-------------|
| Rigidity | 1 ② 3 4 5 |
| Responsiveness | 1 2 3 4 5 |
| Flexion | 1 2 3 (1) 5 |

Flesh

3 - Characteristics

| Thickness: 1 mm | |
|-------------------|--------------------------------|
| Colour: Flesh | Ref X3 : PO1CFLUX_10_CH |
| Thickness: 1.2 mm | |
| Colour: Flesh | Ref X3 : P01CFLUX_12_CH |
| | |

Sheet size: 750 mm x 1000 mm



The size, thickness, colour and other technical data stated for the materials may vary between manufacturing batches (tolerance of +/- 30%).

CONTACTS

PODIATECH SALES DEPARTMENT
PA Champfeuillet EST - 18, rue Léon Béridot
38509 VOIRON CEDEX - France - Tel.: +33 (0)4 76 67 07 15 or 23 podiatech@sidas.com

