

PORON® XRD

FILTER

1 - Material description

Used in a number of applications, Poron® XRD is a material known for its comfort when stationary and its good shock-absorbing properties during more intense activity. It can also be used preventively by people who are required to stand for prolonged periods.

2 - Technical information

 $\ensuremath{\mathsf{Poron}}^{\ensuremath{\$}}$ XRD is a cellular polyurethane. It has one roughened side for easier gluing.

Shore A	Density
Propulsion	 100% 80% 60% 40% Propellant material: > 40% rebound Cushioning material: < 10% rebound Between 10 and 40%: standard material (neither propellant nor cushioning)
Resistance	1 2 3 4 5
Cushioning	

3 - Characteristics

Thickness: 3 mm Colour: Yellow

Ref X3 : PO1HPORONXRD_3_JN

Sheet size: 680 mm x 500 mm




The size, thickness, colour and other technical data stated for the materials may vary between manufacturing batches (tolerance of +/- 30%).

CONTACTS

PODIATECH SALES DEPARTMENT PA Champfeuillet EST - 18, rue Léon Béridot 38509 VOIRON CEDEX – France - Tel.: +33 (0)4 76 67 07 15 or 23 podiatech@sidas.com

SIDAS SAS, Capital €600,000 - APE code 3250 A - CORP. & TRADE REG. No. 304 577 661 00073 - Grenoble INTERCOM. VAT No. FR 76 304 577 661 REF FTMENG 08/16





yellow

Our expertise with you every step of the way

www.podiatech.com